
Volta Zero 16t / 18t technical sheet





VEHICLE		FEATURES	
Fuel Type	Electric	Cabin	
Battery Size std. I long range (kWh)	164 (gross) 246 (gross) 150 (usable) 225 (usable)	Low Entry & Walkthrough Cabin	Heated Steering Wheel
Range std. I long (km / mi) *	200 / 124 280 / 174	Sliding Doors	Air Conditioning
Drive train	Electric rear axle, 250kW, with regeneration	Driver Airbag	Electronic Parking Brake with Auto Hold / Hill Hold
Max Speed (kph / mph)	90 / 56	Heated Windscreen	Satellite Navigation
Seats	3	Heated Seat / Ventilated / Air suspended	Touch Screen Vehicle Controls
Driver Position	Central		
Wheelbase short (mm)	4.800	Safety / Security	
Wheelbase long (mm)	5.900	Rear View Cameras (interior and side) Front and Rear Parking Sensors	Bi-LED Dipped and Main Beam Automatic Headlamps
Total Height until roof cowl standard (mm)	3.302		Payload weight monitoring
Total Height until roof cowl low (mm)	3.193	Reversing Camera	NFC Key Card
Total Length short wheelbase (mm)	9.252	Connectivity	
Total Length long wheelbase (mm)	10.352	Remote Data Logging Capabilities	
Total Width I incl. mirror camera (mm)	2.550 2.819	OPTIONAL FEATURES	
Turning Circle short wheelbase – k2k (m)	15,8	Long Range Battery	Juice Booster
Turning Circle long wheelbase – k2k (m)	19,0	Openable side windows (one side / both sides)	Red Seat Belt
Gross Vehicle Weight (kg)	16.000 / 18.000	360° camera (depending on box type)	Spare Wheel
Front Axle Capacity (kg)	6.500 / 7.650	Digital Video Recorder with Internal Cabin Camera	HV power connector for box equipment (eg. cooling unit, heater,)
Rear Axle Capacity (kg)	10.500 / 11.500		
Kerb Weight short wheelbase (kg)	6.500 (standard range) I 6.975 (long range)	ADR AT (16t only)	Low roof cowl
Kerb Weight long wheelbase (kg)	6.700 (standard range) 7.175 (long range)	Additional language packages	
Kerb Weight fully built up	To be defined by Body Builder	Body specifications (incl. tail lift, box doors and accessories) to be defined by Body Builder	

Note: All mass and dimensions are valid as of 30/05/2024.
*) The range figures have been proven by customer trials, but depend on several factors including optional equipment, variations in weather, driving styles and vehicle loads, the range can deviate.